



1700

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3-piece foam set
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels
- Hi-density foam tray option for 10 firearms
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles



CONFIGURATIONS



1700
Standard



1700WF
With Foam



1700NF
No Foam




DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 35.76 x 13.73" x 5.35 (90.8 x 34.9 x 13.6 cm) |
| Exterior (L×W×D) | 38.47 x 16.42" x 6.14 (97.7 x 41.7 x 15.6 cm) |
| Int Volume | 1.52 ft³ (0.043 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | | |
|---|--|--|
|  Black |  Desert Tan |  OD Green |
|---|--|--|

WEIGHT

| | |
|-------------------------|--------------------|
| Weight With Foam | 16.85 lbs (7.6 kg) |
| Weight Empty | 15.10 lbs (6.8 kg) |







TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

OTHER

| | |
|-----------------|-----|
| Military | yes |
|-----------------|-----|

ACCESSORIES

| | | | | |
|--|--|--|---|---|
|  1500MP EZ-Click™ MOLLE Panel |  1500CI Corrosion Intercept Kit |  1506TSA TSA Lock |  1500D Desiccant Silica Gel |  1703 Replacement O-ring |
|  LGMT-001P Protector Case Roof Mount | | | | |