



1440

Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Retractable extension trolley handle
- Stainless steel padlock protectors



CONFIGURATIONS



1440
Standard



1444
With Utility Padded Divider Set
& Lid Organizer



1447
With Padded Office Divider Set
& Lid Organizer



1440NF
No Foam



1440WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 17.10 x 7.50" x 16.00 (43.4 x 19.1 x 40.6 cm) |
| Exterior (L×W×D) | 19.70 x 12.00" x 18.00 (50 x 30.5 x 45.7 cm) |
| Lid Depth | 2.00" (5.1 cm) |
| Bottom Depth | 14.00" (35.6 cm) |
| Total Depth | 16" (40.6 cm) |
| Int Volume | 1.19 ft ³ (0.034 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|---------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |

Purge Vent

3 Micron Hydrophobic Non-Woven

COLORS Black

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 16.50 lbs (7.5 kg) |
| Weight Empty | 14.50 lbs (6.6 kg) |
| Buoyancy | 95.30 lbs (43.2 kg) |
| Master Pack Weight | 18.00 lbs (8.2 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

| | |
|--------------------------|-----|
| Wheels | 2 |
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |

ACCESSORIES

1441
6 pc. Replacement Foam Set



1443
Replacement O-ring



1448
Photographer's Lid Organizer



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

