



## 1910

The ultra compact aluminum 1910 flashlight is designed with style and function in mind. Using only a single AAA battery, this bright LED light creates a clean white beam. The high and low light output modes make for an efficient lighting tool; the perfect personal light.

- Unconditional Lifetime Guarantee of Excellence
- Ingress Protected IPX7
- High / Low modes
- Single AAA battery
- On/Off/Momentary Switch



### DIMENSIONS

|        |                |
|--------|----------------|
| Length | 3.80" (9.7 cm) |
|--------|----------------|

### MATERIALS

|        |                                |
|--------|--------------------------------|
| Body   | Aluminum with Type II Anodized |
| O-Ring | EPDM                           |
| Lens   | Polycarbonate (PC)             |
| Shroud | Aluminum with Type II Anodized |
| Clip   | High Carbon Steel              |

### COLORS

|         |
|---------|
| ■ Black |
|---------|

### LIGHT SPECS

|           |     |
|-----------|-----|
| Lamp Type | LED |
|-----------|-----|

### POWER

|                    |          |
|--------------------|----------|
| Battery Size       | AAA      |
| Battery Type       | Alkaline |
| Battery Quantity   | 1        |
| Batteries Included | yes      |
| Volts              | 1.5v     |

### WEIGHT

|                          |                |
|--------------------------|----------------|
| Weight With Batteries    | 1.5 oz (43 gr) |
| Weight Without Batteries | 1.1 oz (31 gr) |

### SWITCH

|             |                  |
|-------------|------------------|
| Switch Type | Momentary Switch |
| Light Modes | On / Off         |

OTHER

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

**Minimum Pack** 6 [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

| FL1 STANDARD  | HIGH          | LOW          |
|---|---------------|--------------|
|    | 106<br>LUMENS | 21<br>LUMENS |
|    | 2h 30mins     | 4h 0mins     |
|    | 55m           | 24m          |
|   | 765cd         | 140cd        |
|  | IPX7          |              |

ACCESSORIES