



## 1400 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware
- Stainless steel padlock protectors



### CONFIGURATIONS



**1400**  
Standard



**1400NF**  
No Foam



**1400WF**  
With Foam

### DIMENSIONS

<b>Interior (L×W×D)</b>	11.81 x 8.87" x 5.18 (30 x 22.5 x 13.2 cm)
<b>Exterior (L×W×D)</b>	13.37 x 11.62" x 6.00 (34 x 29.5 x 15.2 cm)
<b>Lid Depth</b>	1.18" (3 cm)
<b>Bottom Depth</b>	4.00" (10.2 cm)
<b>Total Depth</b>	5.18" (13.2 cm)
<b>Int Volume</b>	0.31 ft³ (0.009 m³)
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS

Purge Vent

3 Micron Hydrophobic Non-Woven

COLORS

Black  
Silver

Desert Tan  
Yellow

Orange

OD Green

WEIGHT

Weight With Foam 4.41 lbs (2 kg)  
Weight Empty 3.97 lbs (1.8 kg)  
Buoyancy 20.06 lbs (9.1 kg)  
Master Pack Weight 22.60 lbs (10.3 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)  
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67  
MIL C-4150J  
Def Stan 81-41  
ATA 300

OTHER

Master Pack 4  
Nameplate yes  
Military yes

ACCESSORIES



**1401**  
3 pc. Replacement Foam Set



**1403**  
Replacement O-ring



**1400PF**  
Special Application Panel  
Frame



**1400TPKIT**  
TrekPak Case Divider Kit



**1400TPDIV**  
Extra TrekPak Dividers



**1507**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1500CI**  
Corrosion Intercept Kit

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-28-24*