

1490CC1

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\rm m}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Double safety locking latches with keys
- Fits notebook computers up to 14.0" $\dot{\text{L}}$ x 10.8" W x 2.5" D (43.9 x 24.9 x 8.3 cm)
- · Lid organizer, fitted shock absorbing tray, shoulder strap
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware



DIMENSIONS

Interior (L×W×D) 17.75 x 11.37" x 4.12 (45.1 x 28.9 x 10.5 cm) Exterior (L×W×D) 19.87 x 13.93" x 4.68 (50.5 x 35.4 x 11.9 cm)

 Lid Depth
 1.50" (3.8 cm)

 Bottom Depth
 2.62" (6.7 cm)

 Total Depth
 4.12" (10.5 cm)

 Int Volume
 0.48 ft³ (0.014 m³)

MATERIALS

Body ABS
Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 6.50 lbs (2.9 kg)

 Weight Empty
 5.47 lbs (2.5 kg)

 Buoyancy
 41.00 lbs (18.6 kg)

 Master Pack Weight
 27.30 lbs (12.4 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

Def Stan 81-41

OTHER

Master Pack4NameplateyesMilitaryyes

ACCESSORIES







1498 Computer Lid Organizer



1499CComputer Bottom Insert



1472 Shoulder Strap



1506TSA TSA Lock



1500D Desiccant Silica Gel



1500CICorrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-29-24