

1646

Air

Pelican understands that finding the right protection, with the perfect fit for your gear, is a priority. Pelican™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Pelican's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Pelican's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Pelican has you covered.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- · Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- · Made in the USA



DIMENSIONS

 Interior (L×W×D)
 32.06 x 15.87" x 13.42 (81.4 x 40.3 x 34.1 cm)

 Exterior (L×W×D)
 35.29 x 19.00" x 15.08 (89.6 x 48.3 x 38.3 cm)

 Lid Depth
 1.98" (5 cm)

 Bottom Depth
 11.44" (29.1 cm)

 Total Depth
 13.42" (34.1 cm)

 Int Volume
 3.95 ft³ (0.112 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM
Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 25.70 lbs (11.7 kg)

 Weight Empty
 20.50 lbs (9.3 kg)

 Buoyancy
 263.00 lbs (119.3 kg)

TEMPERATURE

Pelican

Minimum Temperature • Torrance CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Maximum Temperature 160°F (71.1 °C) sales@pelican.com • www.pelican.com

Document created on 05-09-24

ACCESSORIES