

1510LOC

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\rm m}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 2 in 1 protection: detachable computer sleeve and accessories pouch
- Maximum airline carry on size*
- · Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Fits notebook computers up to 14.4" x 11.1" x 1.7" (36.58 x 28.19 x 4.32 cm)
- * Check with your airline for exact measurement requirements.



DIMENSIONS

 Interior (L×W×D)
 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm)

 Exterior (L×W×D)
 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)

 Lid Depth
 1.79" (4.5 cm)

 Bottom Depth
 5.79" (14.7 cm)

 Total Depth
 7.58" (19.3 cm)

 Int Volume
 0.96 ft³ (0.027 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

Weight With Foam 13.60 lbs (6.2 kg)

 Weight Empty
 11.99 lbs (5.4 kg)

 Buoyancy
 64.15 lbs (29.1 kg)

 Master Pack Weight
 32.43 lbs (14.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels2Extendable HandleyesMaster Pack2NameplateyesReduced AreayesMilitaryyes

ACCESSORIES



1513 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



1500CICorrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-22-24