

1780

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · 4 strong polyurethane wheels with stainless steel bearings
- The new class of XXL Pelican Transport Cases
- · Watertight, crushproof, and dustproof
- 50/50 lid-to-base ratio for easy loading
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Completely detachable lid for full access
- · Easy open double-throw latches
- Fold down handles
- Lifetime Guarantee of Excellence
- O-ring seal
- · Open cell core with solid wall design strong, light weight
- Stainless steel padlock protectors



CONFIGURATIONS



1780 Standard



1780NF No Foam



1780WF With Foam

DIMENSIONS

Interior (L×W×D) 41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm) Exterior (L×W×D) 44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)

 Lid Depth
 7.58" (19.3 cm)

 Bottom Depth
 7.30" (18.5 cm)

 Total Depth
 14.88" (37.8 cm)

 Int Volume
 7.63 ft³ (0.216 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch EXL O-Ring Polymer

PinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 49.00 lbs (22.2 kg)

 Weight Empty
 38.40 lbs (17.4 kg)

 Buoyancy
 500.00 lbs (226.8 kg)

 Master Pack Weight
 56.00 lbs (25.4 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

Def Stan 81-41

OTHER

Wheels 4
Master Pack 1
Nameplate yes

ACCESSORIES



1781 6 pc. Replacement Foam Set



1782Pick N Pluck™ Sections Only (set of 4)



1783 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



1500CICorrosion Intercept Kit

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-01-24