

# 1510M

#### **Protector**

**Mobility Case** 

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican  $^{\text{\tiny TM}}$  Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- $\bullet$  4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings
- The Mobility Version of the 1510 Case is over the maximum FAA carry on size
- · Water resistant, crushproof, and dust resistant
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- \* Check with your airline for exact measurement requirements.



### **CONFIGURATIONS**



**1510M** Standard



**1510MNF** No Foam



**1510MWF** With Foam

#### **DIMENSIONS**

Interior (L×W×D) 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) Exterior (L×W×D) 23.55 x 14.36" x 10.62 (59.8 x 36.5 x 27 cm)

 Lid Depth
 1.79" (4.5 cm)

 Bottom Depth
 5.79" (14.7 cm)

 Total Depth
 7.58" (19.3 cm)

 Int Volume
 0.96 ft³ (0.027 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

## **COLORS**

Black

### WEIGHT

Weight With Foam 17.91 lbs (8.1 kg)
Weight Empty 16.30 lbs (7.4 kg)

#### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

#### **CERTIFICATIONS**

IP57

### OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes
Military yes

#### **ACCESSORIES**



**1511** 4 pc. Replacement Foam Set



**1513** Replacement O-ring



**1515** Padded Divider Set



**1519** Lid Organizer



**1507** Quick Mounts - set of 4







**1500D** Desiccant Silica Gel



**1500CI**Corrosion Intercept Kit



**1510TPKIT** TrekPak Case Divider Kit



**1510TPDIV** Extra TrekPak Dividers

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-04-24