

9480

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- 3 pre-set light output levels Up to 4,000 lumens (calculated)
- Up to 28 hrs of run time Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
 Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply



DIMENSIONS

Head (L×W×D)	8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (L×W×D)	15.50 x 6.50" x 10.25 (39.4 x 16.5 x 26 cm)
Light Head Height (max)	23.75" (60.3 cm)

MATERIALS

Body	Polypropylene	
Head	Aluminum	
Mast	Aluminum	
Lens	Polycarbonate (PC)	

COLORS

Black

Yellow

LIGHT SPECS

Lumens (High)	4000
Lumens (Med)	3000
Lumens (Low)	1000
	1000
Lamp Heads	1
Lamp Type	LED
Number of LEDs	8
Beam Spread	125°
IP Rating	54
5	

POWER

Run Time (High)	6.00 hrs
Run Time (Med)	8.00 hrs
Run Time (Low)	28.00 hrs
Battery Type	Sealed Lead Acid (SLA)

Rechargeable	yes
Battery Lifespan	500 cycles
Charge Time	8 hrs
Battery Level Indicator	Full-time battery level display and low battery warning (visible flashing)
Sockets (Primary)	1
Volts	12.0v

WEIGHT

Weight

27.50 lbs (12.5 kg)

SWITCH

Switch Type Light Modes Silicone Rubber Keypad High / Medium / Low / Flashing

ACCESSORIES



 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 05-17-24