

9490

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
- Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)



DIMENSIONS

 Head (L×W×D)
 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)

 Closed (L×W×D)
 20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm)

Light Head Height

(max)

72.00" (182.9 cm)

MATERIALS

BodyPolypropyleneHeadAluminumMastAluminum

Lens Polycarbonate (PC)

COLORS

Black Yellow

LIGHT SPECS

Lumens (High)6000Lamp Heads1Lamp TypeLEDNumber of LEDs10Beam Spread125°IP Rating54

POWER

 Run Time (High)
 3.50 hrs

 Run Time (Med)
 12.00 hrs

 Run Time (Low)
 24.00 hrs

Battery Type Sealed Lead Acid (SLA)

Rechargeable yes **Battery Lifespan** 500 cycles

Charge Time 8 hrs

Battery Level Indicator Full-time battery level display and low battery warning (visible flashing)

Sockets (Primary) 1 Volts 12.0v

WEIGHT


Weight 32.00 lbs (14.5 kg)

SWITCH

Switch TypeSilicone Rubber KeypadLight ModesHigh / Medium / Low / Flashing

ACCESSORIES







9489 Powerpack



9447 DC Vehicle Charger Cord

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-18-24