

# 1465 Air

Pelican<sup>™</sup> Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 45 years Pelican has designed and crafted the most influential protective cases in

the world, and we're just getting started. With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Fold down over-molded handle
- Stainless steel padlock protectors
  Press and Pull<sup>™</sup> Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2™</sup> Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck<sup>™</sup> foam
- Waterproof, crushproof, dustproof
- Made in the USA



#### DIMENSIONS

| 18.62 x 9.99" x 10.93 (47.3 x 25.4 x 27.8 cm)  |
|--|
| 20.83 x 12.62" x 12.75 (52.9 x 32.1 x 32.4 cm) |
| 4.94" (12.5 cm)                                |
| 5.99" (15.2 cm)                                |
| 10.93" (27.8 cm)                               |
| 1.18 ft³ (0.033 m³)                            |
| 0.31" (0.8 cm)                                 |
|  |

### MATERIALS

| Body       | Proprietary Polypropylene Blend                 |
|------------|---|
| Latch      | ABS   |
| O-Ring     | EPDM  |
| Pins       | Stainless Steel                                 |
| Foam       | Polyurethane                                    |
| Purge Body | ABS   |
| Purge Vent | Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven |

#### COLORS

Black

#### WEIGHT

| Weight With Foam | 8.78 lbs (4 kg)     |
|------------------|---------------------|
| Weight Empty     | 7.12 lbs (3.2 kg)   |
| Buoyancy         | 82.00 lbs (37.2 kg) |

## TEMPERATURE

Minimum Temperature-60°F (-51.1 °C)Maximum Temperature160°F (71.1 °C)

ACCESSORIES



PL2 Padlock (2 pack)

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 05-16-24