

1470

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Double safety locking latches with keys
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



DIMENSIONS

Interior (L×W×D) 15.70 x 10.70" x 3.87 (39.9 x 27.2 x 9.8 cm) Exterior (L×W×D) 16.88 x 13.23" x 4.47 (42.9 x 33.6 x 11.4 cm)

 Lid Depth
 1.47" (3.7 cm)

 Bottom Depth
 2.40" (6.1 cm)

 Total Depth
 3.87" (9.8 cm)

 Int Volume
 0.38 ft³ (0.011 m³)

 Padlock Hole Diameter
 0.25" (0.6 cm)

MATERIALS

Body ABS
Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 5.51 lbs (2.5 kg)

 Weight Empty
 4.28 lbs (1.9 kg)

 Buoyancy
 24.91 lbs (11.3 kg)

 Master Pack Weight
 22.20 lbs (10.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

MIL C-4150J

OTHER

Master Pack4NameplateyesMilitaryyes

ACCESSORIES











1471 3 pc. Replacement Foam Set

1472 Shoulder Strap

1473 Replacement O-ring

1470PFSpecial Application Panel Frame

1507 Quick Mounts - set of 4







1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-19-24