

0550

Protector

Transport Case

With over 11 cubic feet (0.311 cubic meters) of space, you can store, protect, and move large loads in seconds. The reinforced honeycomb deck and lid construction provide support for heavy equipment, or multiple stacking on a 463L pallet. Opening the case at any altitude is not a problem- the dual integrated automatic pressure equalization valves keep moisture out and prevent vacuum lock, and the double wide grip makes lifting easy. With an IP55 certification, the 0550 Transport Case will protect your gear against rain and dirt. The 0550 Transport Case: Built to move-by forklift, by wheel, by hand.

- Built to move: by forklift, by wheel or by hand
- Fit six 0550 Cases per 463L military pallet, 18 when stacked!
- Over 11ft3 (.311m3) of storage space
- Dual Integrated Automatic Pressure Equalization Valves
- Easy open double-throw latches
- Four extra-deep base-to-lid locking cleats ensure maximum stacking stability
- Lifetime Guarantee of Excellence
- Locking metal Lidstays keep lid locked in open position
- O-ring seal for dust and water resistant seal (IP55)
- Open cell core with solid wall design strong, light weight
- Optional Caster Wheel Kit complete with brakes
- Optional Pallet Riser Kit
- Reinforced honeycomb deck and lid for added strength
- Stainless steel hardware and padlock protectors
- Store documents outside the case with our Document Container



DIMENSIONS

Interior (L×W×D) 47.57 x 24.07" x 17.68 (120.8 x 61.1 x 44.9 cm) Exterior (L×W×D) 51.05 x 27.54" x 22.79 (129.7 x 70 x 57.9 cm)

 Lid Depth
 3.19" (8.1 cm)

 Bottom Depth
 14.49" (36.8 cm)

 Total Depth
 17.68" (44.9 cm)

 Int Volume
 11.72 ft³ (0.332 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless Steel

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

Black

WEIGHT

Weight With Foam 95.00 lbs (43.1 kg)

 Weight Empty
 79.20 lbs (35.9 kg)

 Buoyancy
 820.00 lbs (371.9 kg)

 Master Pack Weight
 95.00 lbs (43.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

OTHER

Master Pack 1

ACCESSORIES











0507 Caster Wheel Kit

0508 Pallet Riser Kit

0551 6 pc. Replacement Foam Set

1630DCDocument Container
Accessory

1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-06-24