

1490CC1 Protector Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Double safety locking latches with keys
- Fits notebook computers up to 14.0" L x 10.8" W x 2.5" D (43.9 x
- 24.9 x 8.3 cm)
- Lid organizer, fitted shock absorbing tray, shoulder strap
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware



DIMENSIONS

| :m) |
|-----|
| :m) |
| |
| |
| |
| |
| |

MATERIALS

| ABS |
|--------------------------------|
| ABS |
| Polymer |
| Stainless Steel |
| 1.3 lb Polyurethane |
| ABS |
| 3 Micron Hydrophobic Non-Woven |
| |

COLORS

Black

WEIGHT

| Weight With Foam | 6.50 lbs (2.9 kg) |
|--------------------|---------------------|
| Weight Empty | 5.47 lbs (2.5 kg) |
| Buoyancy | 41.00 lbs (18.6 kg) |
| Master Pack Weight | 27.30 lbs (12.4 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

Def Stan 81-41

OTHER

| Master Pack | 4 |
|-------------|-----|
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1493

Replacement O-ring



1498

Computer Lid Organizer



1499C Computer Bottom Insert







1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-05-24