

3325

Compact / Safety Certified / Tail Switch Design - All three are

combined in the 3325 LED flashlight

The compact and lightweight design begins with the use of only 3 AA alkaline batteries and yet produces over 162 lumens of brilliant light. Safety certified for use in most volatile work environments. The rear mounted switch make the 3325 a perfect match for any helmet mounted applications. The photoluminescent ("glow in the dark") shroud ensures you'll be able to locate your light even in the darkest of conditions. For added reliability, an IPX7 ingress protection level will protect the 3325 in the most severe weather conditions. Backed by Pelican's Lifetime Guarantee makes the 3325 a true value!



- 3 AA Batteries (Included)
- · Glow-in-the-dark shroud
- Tail switch for easy one-handed operation
- Pelican Products, Inc.'s Lifetime Guarantee
- Ingress Protected IPX7
- Class I, Class II, Class III Division 1 Safety Certified

DIMENSIONS

Length 6.06" (15.4 cm)

MATERIALS

Body EXL O-Ring EPDM

Lens Polycarbonate (PC)

Shroud Photo luminescent Polycarbonate (PC)

COLORS

High Visibility Yellow

LIGHT SPECS

Lamp Type LED

POWER

Battery Size AA
Battery Type Alkaline
Battery Quantity 3
Batteries Included yes
Volts 4.5v

WEIGHT

Weight With Batteries 6.1 oz (173 gr)
Weight Without
Batteries 3.6 oz (102 gr)

SWITCH

Switch TypePush ButtonLight ModesOn / Off

CERTIFICATIONS

Class I, Division 1

IECEx ia

Class II, Division 1 Class III, Division 1

OTHER

Minimum Pack1Package CodeC

FL1 STANDARD	HIGH
314	171 LUMENS
	16h 0mins
	136m
	4558cd
The	IPX7

ACCESSORIES







2407 Nylon Holster

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-08-24