



## 3335R

The Pelican™ 3335R is a small & light rechargeable intrinsically safe work light. The compact design fits comfortably in your hand and has the power to get you through the worst conditions, safely. The 3335R boasts performance built in providing up to 246 lumens or 58 hours of continuous run time. 3 modes are provided, High / Low / Flashing. There is a full-time battery level indicator built into the power switch, so you'll always know when it's time to recharge. The Right-Angle Adapter accessory (#3317, sold separately) transforms the flashlight into a wearable work light that allows the head to articulate, directing the light exactly where you need it.

- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Lanyard (included)
- IP67 Rating
- Up to 246 Lumens
- Right-Angle Accessory (#3317, sold separately) transforms the 3335R into hands free wearable flashlight with head rotation capability
- Up to 58 hours run time
- Safety Certified Class I, Division 1 / IECEx ia/InMetro
- Lithium-Ion rechargeable battery included




### DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 6.11" (15.5 cm) |
|---------------|-----------------|

### MATERIALS

|               |                                       |
|---------------|---------------------------------------|
| <b>Body</b>   | Anti-static Impact Modified PC/PBT    |
| <b>O-Ring</b> | EPDM                                  |
| <b>Lens</b>   | Anti-static coated Polycarbonate (PC) |
| <b>Shroud</b> | Anti-static Impact Modified PC/PBT    |

### COLORS

|                                                                                     |                        |
|-------------------------------------------------------------------------------------|------------------------|
|  | High Visibility Yellow |
|-------------------------------------------------------------------------------------|------------------------|

### LIGHT SPECS

|                  |     |
|------------------|-----|
| <b>Lamp Type</b> | LED |
|------------------|-----|

### POWER






|                                |             |
|--------------------------------|-------------|
| <b>Battery Size</b>            | 18650       |
| <b>Battery Type</b>            | Lithium-Ion |
| <b>Battery Quantity</b>        | 1           |
| <b>Batteries Included</b>      | yes         |
| <b>Rechargeable</b>            | yes         |
| <b>Charge Time</b>             | 12 hrs      |
| <b>Battery Level Indicator</b> | RGB LED     |
| <b>Volts</b>                   | 3.7v        |

WEIGHT

|                          |                 |
|--------------------------|-----------------|
| Weight With Batteries    | 4.6 oz (130 gr) |
| Weight Without Batteries | 3.0 oz (85 gr)  |

SWITCH

|             |                       |
|-------------|-----------------------|
| Switch Type | Push Button           |
| Light Modes | High / Low / Flashing |

| FL1 STANDARD                                                                        | HIGH       | LOW       |
|-------------------------------------------------------------------------------------|------------|-----------|
|    | 246 LUMENS | 30 LUMENS |
|    | 6h 15mins  | 58h 0mins |
|   | 151m       | 51m       |
|  | 5718cd     | 649cd     |
|  | IP67       |           |

ACCESSORIES



**3317**  
Right Angle Adapter

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-19-24*