

Uncontrolled document as of May 18, 2006. Refer to website for up to date specifications.



Little Ed™ 3600

Don't be fooled by the name. This right angle light packs a punch. The 3600 is made of ABS resin that's extremely strong, light weight, corrosion proof, and resistant to extreme temperatures. The super bright Xenon beam cuts through thick smoke and dust and the one-handed switch is easy to operate, even with gloves. For hands-free use, a stainless steel clip is built in. Attach the Little Ed to your turnout coat or work shirt. It is powered by 4 AA alkaline cells (included).

**Minimum Pack 1 ea.
Packaged Weight: 11.7 oz.**

Little Ed™ 3600 Configurations

Cat. #	Description	Sug. Retail
3600	Little Ed™ 3600 (Carded)	\$44.75
3600PL	Little Ed™ 3600 w/ Photoluminescent Shroud	\$48.95



Little Ed™ 3600 Specifications

Light Source	Tested Lumen Value	Tested Lux Value
Xenon	25.0	5,800

Batteries	Battery Burn Time	Battery Pack/Charging Time
4 AA Alkaline (Included)	4 hrs.	N/A

Watts	Voltage
3.2	6

Length	Weight w/Batteries	Weight w/o Batteries
7.51" (19.1 cm)	10.1 oz. (0.29 kg)	6.6 oz. (0.19 kg)

Little Ed™ 3600 Approvals

CE Ex II 3 GD T 135°C EEx nL IIC T4
Certificate: Epsilon 02ATEX1182X/3

SP Class I; Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G -35° TO +40°C.

UL Class I Div. 2 Listed 4S67/E184884 Class I; Div. 2; Gp. D / Class I; Zone 2; Gp. IIA; T3

Little Ed™ 3600 Accessories

Cat. #	Description	Sug. Retail
2404	Little Ed™ 3600 Lamp Module	\$12.35
2403PL	Photoluminescent Shroud	\$7.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
 e-mail: sales@pelican.com • www.pelican.com