



## 9410L

### LESS THAN 3 LBS + 1203 LUMENS = BRIGHTEST & LIGHTEST IN ITS CLASS

At less than 3 pounds and 1203 lumens, the new 9410L LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Lithium-Ion batteries illuminate a distance of 475 yards (435 meters). And it's loaded with innovative technology and features you have come to expect from Pelican. Whether you're on a USAR team or the 3rd shift at a refinery, you'll appreciate the compact size and high output of the new 9410L LED Lantern.

### Approved to NFPA (National Fire Protection Association) 1901

- Built Pelican tough
- Super bright LED beam
- Up to 1018 lumens (with 2x CR123 batteries)



### DIMENSIONS

Length	8.75" (22.2 cm)
--------	-----------------

### MATERIALS

Body	ABS
O-Ring	EPDM
Lens	Polycarbonate (PC)
Shroud	EXL

### COLOURS

 Black	 High Visibility Yellow
---	--

### LIGHT SPECS

Lamp Type	LED
-----------	-----

### POWER

Battery Size	18650
Battery Type	Lithium-Ion
Battery Quantity	6
Batteries Included	yes
Rechargeable	yes
Charge Time	8 hrs
Battery Level Indicator	RGB LED
Volts	7.2v

### WEIGHT







Weight With Batteries	44.7 oz (1267 gr)
Weight Without Batteries	0.0 oz (0 gr)

SWITCH






Switch Type	Push Button
Light Modes	High / Low / Flashing

OTHER

Minimum Pack	1
Package Code	B

FL1 STANDARD	HIGH	LOW
	1203 LUMENS	553 LUMENS
	4h 30mins	10h 30mins
	430m	287m
	46328cd	20616cd
	1m	
	IPX4	

ACCESSORIES

				
8056F 12v Plug-in for Fast Charger	9419L Replacement Battery	9416L Deck/Dash Charger Base Unit	6061F Direct Wiring Rig for Fast Charger	6058A 220V Transformer (Australia)

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 04-25-24*