



9480

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- 3 pre-set light output levels
- Up to 4,000 lumens (calculated)
- Up to 28 hrs of run time
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply




DIMENSIONS

Head (LxWxD)	8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (LxWxD)	15.50 x 6.50" x 10.25 (39.4 x 16.5 x 26 cm)
Light Head Height (max)	23.75" (60.3 cm)

MATERIALS

Body	Polypropylene
Head	Aluminum
Mast	Aluminum
Lens	Polycarbonate (PC)

COLOURS

 Black	 Yellow
---	--

LIGHT SPECS

Lumens (High)	4000
Lumens (Med)	3000
Lumens (Low)	1000
Lamp Heads	1
Lamp Type	LED
Number of LEDs	8
Beam Spread	125°
IP Rating	54

POWER

Run Time (High)	6.00 hrs
Run Time (Med)	8.00 hrs
Run Time (Low)	28.00 hrs
Battery Type	Sealed Lead Acid (SLA)

Rechargeable	yes
Battery Lifespan	500 cycles
Charge Time	8 hrs
Battery Level Indicator	Full-time battery level display and low battery warning (visible flashing)
Sockets (Primary)	1
Volts	12.0v

WEIGHT

Weight	27.50 lbs (12.5 kg)
---------------	---------------------

SWITCH

Switch Type	Silicone Rubber Keypad
Light Modes	High / Medium / Low / Flashing

ACCESSORIES



9447
DC Vehicle Charger Cord



9487
Padded Shoulder Strap



9489
Powerpack

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-20-24