

9490

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- Full time battery level indication with low level flashing indicator
 Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
 Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)



DIMENSIONS

Head (L×W×D)	8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (L×W×D)	20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm)
Light Head Height (max)	72.00" (182.9 cm)

MATERIALS

Body Head	Polypropylene Aluminum	
Mast	Aluminum	
Lens	Polycarbonate (PC)	

COLOURS

Black

Yellow

LIGHT SPECS

Lumens (High)	6000	
Lamp Heads	1	
Lamp Type	LED	
Number of LEDs	10	
Beam Spread	125°	
IP Rating	54	

POWER

Run Time (High)	3.50 hrs
Run Time (Med)	12.00 hrs
Run Time (Low)	24.00 hrs
Battery Type	Sealed Lead Acid (SLA)
Rechargeable	yes
Battery Lifespan	500 cycles

Charge Time	8 hrs
Battery Level Indicator	Full-time battery level display and low battery warning (visible flashing)
Sockets (Primary)	1
Volts	12.0v

WEIGHT

Weight

32.00 lbs (14.5 kg)

SWITCH

Switch Type	Silicone Rubber Keypad
Light Modes	High / Medium / Low / Flashing

ACCESSORIES





9487 Padded Shoulder Strap **9489** Powerpack



9447 DC Vehicle Charger Cord

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 04-26-24