

9435

Pelican builds the most safety approved handheld lights on the market. With the 9435, we produce one of the world's first battery powered, safety certified remote area light. It's 1500 lumens illuminate hazardous locations, and with two power settings the 9435 extends run time up to 10 hrs. of clean even light.

At Pelican, designing a lighting system that's safe to use in volatile situations isn't optional. It's fundamental to our philosophy.

**The repair of the 9435 needs to be conducted by a certified Pelican Products repair center due to the requirements of the safety certificate.

- Up to 10 hours run time
- NiMH rechargeable battery
- High / Low lighting modes
- · Low battery indicator
- Class I Division 2, ATEX Zone 2, IECEx ic safety certified
- Up to 1,500 lumens
- · Hi Vis safety orange



DIMENSIONS

Head (L×W×D) 6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm)
Closed (L×W×D) 15.75 x 7.87" x 9.06 (40 x 20 x 23 cm)

Light Head Height

(max)

32.28" (82 cm)

Cord Length 13.78" (35 cm)

MATERIALS

BodyPolycarbonate (PC) / ABSHeadPolycarbonate (PC) / ABSLensPolycarbonate (PC)

COLOURS



LIGHT SPECS

Lumens (High)1500Lumens (Low)750Lamp Heads1Lamp TypeLEDNumber of LEDs18Beam Spread90°IP Rating54

POWER

Run Time (High) 5.00 hrs
Run Time (Low) 10.00 hrs
Battery Type NiMH
Rechargeable yes
Battery Lifespan 300 cycles

Charge Time 8 hrs

Battery Level Indicator Intermittent Blinking

 Sockets (Primary)
 1

 Watts
 18 W

 Volts
 12.0v

WEIGHT

Weight 17.60 lbs (8 kg)

SWITCH

Switch Type Silicone Rubber Keypad

CERTIFICATIONS

Class I, Division 2

IECEx ic
ATEX Zone 2

ACCESSORIES



1460AALG 1460 Case with custom fit foam

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 09-20-24