



## iM3300RFL

### Storm

#### Rifle Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Six Press & Pull Latches
- Guaranteed For Life
- Two Padlockable Hasps
- Three Double-layered, Soft-grip Handles
- Vortex™ Valve
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin
- 20% Deeper Lid



## DIMENSIONS

|                              |                                                |
|------------------------------|------------------------------------------------|
| <b>Interior (L×W×D)</b>      | 50.50 x 14.00" x 6.00 (128.3 x 35.6 x 15.2 cm) |
| <b>Exterior (L×W×D)</b>      | 53.80 x 16.50" x 6.70 (136.7 x 41.9 x 17 cm)   |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                 |
| <b>Bottom Depth</b>          | 4.00" (10.2 cm)                                |
| <b>Total Depth</b>           | 6" (15.2 cm)                                   |
| <b>Int Volume</b>            | 2.45 ft³ (0.069 m³)                            |
| <b>Padlock Hole Diameter</b> | 3/8" (7.6 cm)                                  |

## MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM                                         |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

## COLORS

|                                                                                           |                                                                                              |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
|  Black |  OD Green |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|

## WEIGHT

|                           |                      |
|---------------------------|----------------------|
| <b>Weight With Foam</b>   | 23.00 lbs (10.4 kg)  |
| <b>Weight Empty</b>       | 19.10 lbs (8.7 kg)   |
| <b>Buoyancy</b>           | 153.86 lbs (69.8 kg) |
| <b>Master Pack Weight</b> | 24.50 lbs (11.1 kg)  |

TEMPERATURE

|                     |                  |
|---------------------|------------------|
| Minimum Temperature | -20°F (-28.9 °C) |
| Maximum Temperature | 140°F (60 °C)    |

OTHER

|             |     |
|-------------|-----|
| Master Pack | 1   |
| Military    | yes |

ACCESSORIES

|                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |  |
| <b>iM-STRAP-S-VER2</b><br>Padded Shoulder Strap                                   | <b>iM-LIDSTAY</b><br>Lid Stay                                                     | <b>1506TSA</b><br>TSA Lock                                                        | <b>1500D</b><br>Desiccant Silica Gel                                               | <b>1500CI</b><br>Corrosion Intercept Kit                                            |

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 04-16-24