

## 9415

## 9410L + SAFETY = 9415

# Everything that's great about the 9410L LED Lantern, plus safety certifications

At just 3 pounds and 413\* lumens, the new 9415 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 360 yards (325\* meters). And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety approved for the most volatile work areas, the 9415 LED Lantern is safe and one of the most compact, high output lanterns on the market.

9415 LED Lantern: Lightweight, big LED performance you can trust.

\*Performance data is to FL 1 standards

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Safety Certified Class I, Division I



## DIMENSIONS

8.75" (22.2 cm)

LED

## MATERIALS

Body	ABS	
O-Ring	EPDM	
Lens	Polycarbonate (PC)	
Shroud	EXL	

## COLORS

High Visibility Yellow

## LIGHT SPECS

Lamp Type

#### POWER

Battery Size	С
Battery Type	NiMH
Battery Quantity	4
Batteries Included	yes
Rechargeable	yes
Charge Time	5 hrs 30 mins
Battery Level Indicator	RGB LED
Volts	4.8v

## WEIGHT

Weight With Batteries	49.3 oz (1398 gr)
Weight Without Batteries	0.0 oz (0 gr)

## SWITCH

Switch Type	Push Button	
Light Modes	High / Low / Flashing	

1

В

## CERTIFICATIONS

## Class I, Division 1

## OTHER

Minimum Pack Package Code

FL1 STANDARD	HIGH	LOW
3MZ	413 LUMENS	159 LUMENS
	4h 30mins	12h 0mins
	325m	201m
	26352cd	10076cd
	IPX4	

## ACCESSORIES











**9416** Deck/Dash Charger Base Unit

6057F 110V Transformer (USA)

**6061F** Direct Wiring Rig for Fast Charger

8056F 12v Plug-in for Fast Charger

9418 Replacement Battery

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 04-25-24