

# 3325

# Compact / Safety Certified / Tail Switch Design - All three are

combined in the 3325 LED flashlight

The compact and lightweight design begins with the use of only 3 AA alkaline batteries and yet produces over 162 lumens of brilliant light. Safety certified for use in most volatile work environments. The rear mounted switch make the 3325 a perfect match for any helmet mounted applications. The photoluminescent ("glow in the dark") shroud ensures you'll be able to locate your light even in the darkest of conditions. For added reliability, an IPX7 ingress protection level will protect the 3325 in the most severe weather conditions. Backed by Pelican's Lifetime Guarantee makes the 3325 a true value!



- 3 AA Batteries (Included)
- · Glow-in-the-dark shroud
- Tail switch for easy one-handed operation
- Pelican Products, Inc.'s Lifetime Guarantee
- Ingress Protected IPX7
- Class I, Class II, Class III Division 1 Safety Certified

#### DIMENSIONS

**Length** 6.06" (15.4 cm)

#### **MATERIALS**

Body EXL O-Ring EPDM

**Lens** Polycarbonate (PC)

**Shroud** Photo luminescent Polycarbonate (PC)

#### **COLORS**

High Visibility Yellow

#### LIGHT SPECS

Lamp Type LED

## **POWER**

Battery Size AA
Battery Type Alkaline
Battery Quantity 3
Batteries Included yes
Volts 4.5v

### WEIGHT

Weight With Batteries 6.1 oz (173 gr)
Weight Without
Batteries 3.6 oz (102 gr)

SWITCH Pelican

Switch Type 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Light Modes On / Off sales@pelican.com • www.pelican.com

Document created on 09-20-24

## **CERTIFICATIONS**

Class I, Division 1

**IECEx** ia

Class II, Division 1

Class III, Division 1

## OTHER

FL1 STANDARD	HIGH
31/2	171 LUMENS
$\Theta$	16h 0mins
	136m
	4558cd
The	IPX7

## **ACCESSORIES**