



## 3315R

Ultra compact, special designed lithium rechargeable and safety certified make the Pelican™ 3315R one of the most versatile work lights available today. Its compact design fits comfortably in your hand and requires little space for storage or transport. The 3315R produces up to 132 lumens and provides up to 34 hours of continuous run time. 3 modes are provided, High / Low / Flashing. There is a full time battery level indicator built into the power switch so you'll always know when it's time to recharge. Additionally, there is a right angle adapter accessory (sold separately) that provides hands free lighting. The right angle adapter also allows the light head to articulate, directing the light exactly where you need it.

- IPX7 Waterproof
- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Safety Certified Class I, Division 1 / IECEx ia
- Lanyard (included)
- Articulating right angle adapter with clip (sold separately)
- Special Lithium rechargeable battery provides 2,000 cycles (a 300% increase)
- Up to 132 Lumens
- Up to 34 hours, 15 minutes run time




### DIMENSIONS

<b>Length</b>	6.11" (15.5 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	Anti-static Impact Modified PC/PBT
<b>O-Ring</b>	EPDM
<b>Lens</b>	Anti-static coated Polycarbonate (PC)
<b>Shroud</b>	Anti-static Impact Modified PC/PBT

### COLORS

	High Visibility Yellow
---	------------------------

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	18650
<b>Battery Type</b>	Lithium Iron Phosphate
<b>Battery Quantity</b>	1
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	10 hrs
<b>Battery Level Indicator</b>	RGB LED
<b>Volts</b>	3.2v

WEIGHT

Weight With Batteries	4.6 oz (130 gr)
Weight Without Batteries	3.0 oz (85 gr)

SWITCH






Switch Type	Push Button
Light Modes	High / Low / Flashing

CERTIFICATIONS

Class I, Division 1
IECEX ia
InMetro

OTHER

Minimum Pack	1
Package Code	C

FL1 STANDARD	HIGH	LOW
	132 LUMENS	15 LUMENS
	5h 0mins	34h 0mins
	108m	35m
	2931cd	308cd
	IP67	

ACCESSORIES



**3317**  
Right Angle Adapter



**8056F**  
12v Plug-in for Fast Charger



**3318**  
Deck/Dash Charger Base Unit



**2467F**  
110V Transformer (USA)



**6061F**  
Direct Wiring Rig for Fast Charger

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 04-24-24*