



9435

Pelican builds the most safety approved handheld lights on the market. With the 9435, we produce one of the world's first battery powered, safety certified remote area light. It's 1500 lumens illuminate hazardous locations, and with two power settings the 9435 extends run time up to 10 hrs. of clean even light.

At Pelican, designing a lighting system that's safe to use in volatile situations isn't optional. It's fundamental to our philosophy.

****The repair of the 9435 needs to be conducted by a certified Pelican Products repair center due to the requirements of the safety certificate.**

- Up to 10 hours run time
- NiMH rechargeable battery
- High / Low lighting modes
- Low battery indicator
- Class I Division 2, ATEX Zone 2, IECEx ic safety certified
- Up to 1,500 lumens
- Hi Vis safety orange



DIMENSIONS

Head (LxWxD)	6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm)
Closed (LxWxD)	15.75 x 7.87" x 9.06 (40 x 20 x 23 cm)
Light Head Height (max)	32.28" (82 cm)
Cord Length	13.78" (35 cm)

MATERIALS

Body	Polycarbonate (PC) / ABS
Head	Polycarbonate (PC) / ABS
Lens	Polycarbonate (PC)

COLORS

- Orange

LIGHT SPECS

Lumens (High)	1500
Lumens (Low)	750
Lamp Heads	1
Lamp Type	LED
Number of LEDs	18
Beam Spread	90°
IP Rating	54

POWER

Run Time (High)	5.00 hrs
Run Time (Low)	10.00 hrs
Battery Type	NiMH
Rechargeable	yes
Battery Lifespan	300 cycles

Charge Time	8 hrs
Battery Level Indicator	Intermittent Blinking
Sockets (Primary)	1
Watts	18 W
Volts	12.0v

WEIGHT

Weight	17.60 lbs (8 kg)
---------------	------------------

SWITCH

Switch Type	Silicone Rubber Keypad
--------------------	------------------------

CERTIFICATIONS

Class I, Division 2
IECEX ic
ATEX Zone 2

ACCESSORIES



1460AALG
1460 Case with custom fit foam

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-10-24