



## EX448

Trade Show Tower

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Military style butterfly stainless steel catch and strike latches
- Lockable - stainless steel cable catch with stainless steel cable
- Weather Resistant full EPMD rubber door gasket (durometer shore A53, (hardness) )
- Rugged galvanized steel door hinges coated with zinc plating, clear trivalent chromate
- Large detent area for labeling on front and rear which prevents scraping (scrape proof)
- Stacking ribs enable stacking two high horizontally
- Pelican one year guarantee
- 15% to 20% thicker, naturally reinforced corners and edges for additional impact protection
- Sold exclusively by Silver State Case Company: 844-243-8500
- [www.silverstatecase.com](http://www.silverstatecase.com)



### DIMENSIONS

<b>Interior (LxWxD)</b>	97.94 x 44.88" x 50.26 (248.8 x 114 x 127.7 cm)
<b>Exterior (LxWxD)</b>	108.00 x 48.22" x 58.80 (274.3 x 122.5 x 149.4 cm)
<b>Lid Depth</b>	0.00" (0 cm)
<b>Bottom Depth</b>	0.00" (0 cm)
<b>Total Depth</b>	0" (0 cm)
<b>Int Volume</b>	127.85 ft <sup>3</sup> (3.62 m <sup>3</sup> )

### MATERIALS

<b>Body</b>	RotoMolded Polyethylene
<b>Latch</b>	Steel (Nickel-black Plated)
<b>O-Ring</b>	Silicone Sponge
<b>Foam</b>	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
<b>Purge Body</b>	Aluminum
<b>PRV Valve</b>	.5 PSI Standard, Light Lift .25 PSI
<b>Handle</b>	Heavy Duty Injection Molded Standard
<b>Optional Handles</b>	Stainless Steel Passivate and Stainless Steel Black
<b>Hardware</b>	Yellow Carbon Steel Standard
<b>Optional Hardware</b>	Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black

### COLORS

■ Gray - 133 Fed Std  
26270

### WEIGHT

<b>Weight</b>	372.00 lbs (168.7 kg)
---------------	-----------------------

<b>Buoyancy</b>	0.00 lbs (0 kg)
<b>Master Pack Weight</b>	372.00 lbs (168.7 kg)

## TEMPERATURE

---

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

## OTHER

---

<b>Military</b>	yes
-----------------	-----

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 04-19-24*