



1495

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Combination Lock Information
- **3 dial combination lock included**
- **Fits up to 17" laptops**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Lifetime Guarantee of Excellence
- Padded shoulder strap
- Pick N Pluck™ with convoluted lid foam
- Stainless steel padlock protectors



CONFIGURATIONS



1495
Standard



1495NF
No Foam



1495WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm) |
| Exterior (L×W×D) | 21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm) |
| Lid Depth | 1.12" (2.8 cm) |
| Bottom Depth | 2.68" (6.8 cm) |
| Total Depth | 3.8" (9.7 cm) |
| Int Volume | 0.55 ft³ (0.016 m³) |
| Padlock Hole Diameter | 0.25" (0.6 cm) |

MATERIALS

| | |
|---------------|-----------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |

| | |
|-------------------|--------------------------------|
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | |
|---|--|
|  Black |  Desert Tan |
|---|--|

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 8.37 lbs (3.8 kg) |
| Weight Empty | 7.23 lbs (3.3 kg) |
| Buoyancy | 45.15 lbs (20.5 kg) |
| Master Pack Weight | 23.00 lbs (10.4 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| |
|-----------------------|
| IP67 |
| Def Stan 81-41 |

OTHER

| | |
|--------------------|-----|
| Master Pack | 2 |
| Nameplate | yes |

ACCESSORIES



1472
Shoulder Strap



1481
3 pc. Replacement Foam Set



1483
Replacement O-ring



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

