

1600 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1600 Standard



1604 With Padded Dividers



1600NF No Foam



1600TP With TrekPak Divider System



1600WF With Foam

DIMENSIONS

Interior (L×W×D)	21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm)
Exterior (L×W×D)	24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	6.12" (15.5 cm)
Total Depth	7.87" (20 cm)
Int Volume	1.65 ft ³ (0.047 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Polypropylene
ABS
Polymer
Stainless Steel
1.3 lb Polyurethane
ABS
3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

OTHER

ACCESSORIES



1601 4 pc. Replacement Foam Set



1600TPKIT TrekPak Case Divider Kit



1602 Pick N Pluck™ Sections Only (set of 2)



1510TPDIV Extra TrekPak Dividers



1603 Replacement O-ring



1507 Quick Mounts - set of 4



1605 Padded Divider Set



1506TSA TSA Lock



1609 Lid Organizer



1500D Desiccant Silica Gel



1500CI Corrosion Intercept Kit

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 09-19-24