



## iM3410

### Storm

#### Long Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Guaranteed For Life
- Four Padlockable Hasps
- Three Double-layered, Soft-grip Handles
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin



## CONFIGURATIONS



**iM3410**  
Standard



**iM3410-X0000**  
No Foam



**iM3410-X0001**  
With Foam

## DIMENSIONS

|                              |                                                |
|------------------------------|------------------------------------------------|
| <b>Interior (L×W×D)</b>      | 54.50 x 10.00" x 6.00 (138.4 x 25.4 x 15.2 cm) |
| <b>Exterior (L×W×D)</b>      | 57.74 x 12.71" x 6.67 (146.7 x 32.3 x 16.9 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                 |
| <b>Bottom Depth</b>          | 4.00" (10.2 cm)                                |
| <b>Total Depth</b>           | 6" (15.2 cm)                                   |
| <b>Int Volume</b>            | 1.89 ft <sup>3</sup> (0.054 m <sup>3</sup> )   |
| <b>Padlock Hole Diameter</b> | 0.37" (0.9 cm)                                 |

## MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM                                         |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

COLORS

|                                                                                         |                                                                                            |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
|  Black |  OD Green |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|

WEIGHT

|                         |                    |
|-------------------------|--------------------|
| <b>Weight With Foam</b> | 20.00 lbs (9.1 kg) |
| <b>Weight Empty</b>     | 18.00 lbs (8.2 kg) |

TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

CERTIFICATIONS

|             |
|-------------|
| <b>IP67</b> |
|-------------|

OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 1   |
| <b>Military</b>    | yes |

ACCESSORIES

|                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |
| <b>iM3410-FOAM</b><br>4 pc. Replacement Foam Set                                    | <b>iM-LIDSTAY</b><br>Lid Stay                                                       | <b>1506TSA</b><br>TSA Lock                                                          | <b>1500D</b><br>Desiccant Silica Gel                                                 | <b>1500CI</b><br>Corrosion Intercept Kit                                              |

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 04-26-24