

# 1520 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof

Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Stainless steel hardware and padlock protectors



#### CONFIGURATIONS



1520 Standard



1524 With Padded Dividers



**1526** With Convertible Travel Bag



**1520NF** No Foam



1520WF With Foam


### DIMENSIONS

Interior (L×W×D)	18.06 x 12.89" x 6.72 (45.9 x 32.7 x 17.1 cm)
Exterior (L×W×D)	19.78 x 15.77" x 7.41 (50.2 x 40.1 x 18.8 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	4.93" (12.5 cm)
Total Depth	6.72" (17.1 cm)
Int Volume	0.91 ft <sup>3</sup> (0.026 m <sup>3</sup> )
Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

# COLORS



#### WEIGHT

Weight With Foam	9.35 lbs (4.2 kg)
Weight Empty	8.29 lbs (3.8 kg)
Buoyancy	63.00 lbs (28.6 kg)
Master Pack Weight	23.30 lbs (10.6 kg)

#### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

#### CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41

#### OTHER

Master Pack	2	
Nameplate	yes	
Military	yes	

# ACCESSORIES





**1508** Photographer's Lid Organizer

**1509** Lid Organizer



**1521** 3 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1523 Replacement O-ring



**1506TSA** TSA Lock



**1525** Padded Divider Set



**1500D** Desiccant Silica Gel



**1520TPKIT** TrekPak Case Divider Kit



**1520TPDIV** Extra TrekPak Dividers



**1520PF** Special Application Panel Frame

**1500CI** Corrosion Intercept Kit

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 04-25-24