

# 1120 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

#### • Watertight, crushproof, and dustproof

Automatic pressure equalization valve - balances interior pressure, keeps water out

- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Stainless steel hardware



### CONFIGURATIONS



**1120** Standard



1120NF No Foam



**1120WF** With Foam

#### DIMENSIONS

Interior (L×W×D)	7.29 x 4.78" x 3.33 (18.5 x 12.1 x 8.5 cm)
Exterior (L×W×D)	8.41 x 6.76" x 3.87 (21.4 x 17.2 x 9.8 cm)
Lid Depth	0.50" (1.3 cm)
Bottom Depth	2.56" (6.5 cm)
Total Depth	3.06" (7.8 cm)
Int Volume	0.07 ft <sup>3</sup> (0.002 m <sup>3</sup> )
Padlock Hole Diameter	0.19" (0.5 cm)

#### MATERIALS

Body	Polypropylene
Latch	Polypropylene
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

## COLORS



### WEIGHT

### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

#### CERTIFICATIONS

IP67	
Def Stan 81-41	

### OTHER

Master Pack	6
Military	yes

### ACCESSORIES



**1121** 3 pc. Replacement Foam Set



**1507** Quick Mounts - set of 4



**1123** Replacement O-ring



**1506TSA** TSA Lock



**1120PF** Special Application Panel Frame



**1500D** Desiccant Silica Gel



**1120TPDIV** Extra TrekPak Dividers



1500Cl Corrosion Intercept Kit



**1120TPKIT** TrekPak Case Divider Kit

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 04-24-24