

2410PL StealthLite™

Same features as the StealthLite[™] 2410 LED Flashlight, but outfitted with a lens ring that emits a bright glow in the dark. The new generation photoluminescent material in the plastic absorbs the energy from any light source - fluorescent lights, the sun, or even the flashlight's own beam. No more fumbling in the dark for your flashlight. It is powered by 4 AA alkaline cells (included), submersible, and has an ELX body which resists chemicals, corrosion, and extreme temperatures.

- As bright as a Xenon light with the battery life of an LED
- Built Pelican tough
- Glow-in-the-dark shroud
- Super bright LED beam
- Unconditional Lifetime Guarantee of Excellence
- NOW WITH NEW UPGRADED SPECS
- Waterproof



DIMENSIONS

Length

7.00" (17.8 cm)

MATERIALS

| Body | EXL |
|--------------------------------|--------------------------------------|
| O-Ring | Ethylene Propylene |
| Lens | Polycarbonate (PC) |
| Shroud | Photo luminescent Polycarbonate (PC) |
| Contact Spring Retainer | Stainless Steel / Phosphore Bronze |

COLORS

High Visibility Yellow

LIGHT SPECS

| Lamp Туре | LED | |
|--------------|----------|--|
| POWER | | |
| Battery Size | АА | |
| Battery Type | Alkaline | |

| Battery Type | Alkaline |
|---------------------------|----------|
| Battery Quantity | 4 |
| Batteries Included | yes |
| Volts | 6.0v |
| | |

WEIGHT

| Weight With Batteries | 7.3 oz (207 gr) |
|-----------------------------|-----------------|
| Weight Without Batteries | 3.7 oz (105 gr) |
| Packaged Weight | 8.4 oz (238 gr) |

SWITCH

| Pelican |
|---------|
| |

Switch Type Light Modes On / Off

Document created on 10-31-24

CERTIFICATIONS

| Class I, Division 1 | |
|------------------------------|--|
| Class II, Division 1 | |
| Class III, Division 1 | |
| IECEx ia | |

OTHER

| Submersible | yes |
|--------------|-----|
| Minimum Pack | 6 |
| Package Code | С |

| FL1 STANDARD | HIGH |
|--------------|---------------|
| 3MZ | 183 LUMENS |
| | 5h 45mins |
| | 184m |
| | 8480cd |
| A CAR | IPX7 |

ACCESSORIES