



## BL8653-5010

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- The BL8653-5010 case is a non-configurable roto case. It requires internal metal supports when empty due the size and weight of the case. This case size is available as a custom design.



### DIMENSIONS

---

<b>Interior (LxWxD)</b>	86.00 x 53.00" x 60.00 (218.4 x 134.6 x 152.4 cm)
<b>Exterior (LxWxD)</b>	90.00 x 57.00" x 64.60 (228.6 x 144.8 x 164.1 cm)
<b>Lid Depth</b>	10.00" (25.4 cm)
<b>Bottom Depth</b>	50.00" (127 cm)
<b>Total Depth</b>	60" (152.4 cm)
<b>Int Volume</b>	158.26 ft <sup>3</sup> (4.481 m <sup>3</sup> )

### MATERIALS

---

<b>Body</b>	RotoMolded Polyethylene
<b>Latch</b>	Steel (Nickel-black Plated)
<b>O-Ring</b>	Silicone Sponge
<b>Foam</b>	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
<b>Purge Body</b>	Aluminum
<b>PRV Valve</b>	.5 PSI Standard, Light Lift .25 PSI
<b>Handle</b>	Heavy Duty Injection Molded Standard
<b>Optional Handles</b>	Stainless Steel Passivate and Stainless Steel Black
<b>Hardware</b>	Yellow Carbon Steel Standard
<b>Optional Hardware</b>	Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black

### COLORS

---

■ Gray - 133 Fed Std  
26270

### WEIGHT

---

<b>Weight</b>	287.50 lbs (130.4 kg)
---------------	-----------------------

### TEMPERATURE

---

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

OTHER

---

**Military**

yes

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 10-31-24*