

3415

Right Angle Light

The most versatile intrinsically safe work light in the world.

The 3415 is the ultimate safety certified compact work light. The Class I II III Division 1 certifications provide the security needed for most hazardous locations. The 3415 is equipped with both a spot and flood LED for close-up as well as distance, so you can have wide area light in the immediate work area and still penetrate darkness hundreds of yards away. It can be activated to run one or both LEDs with 3 levels of brightness. The articulating head and built-in clip allows the light to be directed wherever it is needed. The full time battery level indicator ensures you will always know where your battery status is. The Pelican 3415- a professional grade multi-task lighting tool that will help you get the job done- under any circumstances.

- · Articulating Light Head
- Full Time Battery Level Indication
- Class I, Class II, Class III Division 1 Safety Certified
- · Security Lanyard
- · Attached clip
- Split ring installed
- 2 modes: spot, flashing



DIMENSIONS

Length 7.44" (18.9 cm)

MATERIALS

Body ABS O-Ring NBR

Lens Polycarbonate (PC)

Shroud ABS Clip ABS

Contact Spring Retainer Stainless Steel / Phosphore Bronze / Brass Nickel Plate

COLORS

High Visibility Yellow

LIGHT SPECS

Lamp Type LED Lamp Secondary Type LED

POWER

Battery SizeAABattery TypeAlkalineBattery Quantity3Volts4.5v

WEIGHT

Weight With Batteries 9.0 oz (255 gr)

Weight Without Batteries

6.6 oz (187 gr)

SWITCH

Switch Type Push Button
Light Modes High / Flashing

CERTIFICATIONS

Class I, Division 1 Class II, Division 1 Class III, Division 1 IECEx ia

| FL1 STANDARD | SPOT / FLOOD | FLOOD | SPOT |
|--------------|---------------|---------------|---------------|
| 314 | 336 LUMENS | 177 LUMENS | 186 LUMENS |
| | 6h 0mins | 15h 0mins | 14h 0mins |
| | 133m | 37m | 135m |
| | 4418cd | 336cd | 4544cd |
| The same | IPX8 (1m) | | |

Pelican