



IS2917-1103

ISP Case

Shifting loose cargo can slow down your ops and threaten the mission with damaged freight. The new ISP Case from Pelican™ virtually eliminates load movement with a unique Inter-Stacking Pattern (ISP). The patent pending system is compatible across 6 different case sizes from 4 to 25 cubic feet of storage. Equipped with a silicone sponge O-ring and pressure release valves, the ISP Case is impervious to extreme weather and wet conditions.

The system is designed to maximize the volume of standard logistics platforms. Whether loading standard pallets, NATO pallets, JMIC containers, 463L pallets or sea containers, the ISP Case system will make the most efficient use of cargo space.

With its Inter-Stacking Pattern there is no question where the next case belongs. The disc pattern bottom mates with the wave pattern on the case below, literally falling and locking into place. Cross-stacking builds incredibly tight loads that can save time with strapping or netting.


- Standard Features:
 - Removable Lid
 - Freebreathing
 - Black Carbon Steel, All Catch and Strike Hardware
 - 6 Large Injection Molded Comfort Grip handles
 - Colors: BLACK_032, GREY_133, OLIVE DRAB_137, RED_130, TAN_250
 - Molded-In Edge Casters
 - Inter-Stacking Pattern Cases for NATO pallets, JMIC containers, 463L pallets or sea containers
- Configurable Features:
 - Hardware: Black Stainless Steel
 - Pressure Relief Valve (PRV) with Closed Gasket
 - Hinged Lid
 - Metal Handles: Black Stainless Steel
 - 2 Cable Catch locks per case
 - 2 Padlock Hasps per case
 - 3" X 5" Horizontal Card Holder
 - Front Labels, STD Labels and ATA Labels
 - Pressure Relief Valve
 - Humidity Indicator



CONFIGURATIONS



IS2917-1103
Standard



IS2917-1103-No-Foam
No Foam

DIMENSIONS






Interior (L×W×D)	29.00 x 17.00" x 14.00 (73.7 x 43.2 x 35.6 cm)
Exterior (L×W×D)	32.00 x 20.00" x 16.00 (81.3 x 50.8 x 40.6 cm)

Lid Depth	3.00" (7.6 cm)
Bottom Depth	11.00" (27.9 cm)
Total Depth	14" (35.6 cm)
Int Volume	3.99 ft ³ (0.113 m ³)

MATERIALS

Body	RotoMolded Polyethylene
Latch	Steel (Nickel-black Plated)
O-Ring	Silicone Sponge
Pins	Stainless Steel
Pins (Alt)	Aluminum
Purge Body	Aluminum

COLORS

 Black - 032 Fed Std 27040	 Olive Drab - 137 Fed Std 34096	 Gray - 133 Fed Std 26270	 Tan - 250 Fed Std 20372
 Red - 130 Fed Std 21105			

WEIGHT

Weight With Foam	35.00 lbs (15.9 kg)
Weight Empty	26.00 lbs (11.8 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F

OTHER

Wheels	2
Max Drag Weight	150.00

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-18-24