



1430

Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Unique top loading design**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Optional shoulder strap available



CONFIGURATIONS



1430
Standard



1434
With Padded Dividers & Lid Organizer



1437
With Padded Office Divider Set & Lid Organizer



1430NF
No Foam



1430WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm) |
| Exterior (L×W×D) | 16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm) |
| Lid Depth | 2.00" (5.1 cm) |
| Bottom Depth | 9.70" (24.6 cm) |
| Total Depth | 11.7" (29.7 cm) |
| Int Volume | 0.53 ft³ (0.015 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|---------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |

Purge Vent

3 Micron Hydrophobic Non-Woven

COLORS Black

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 6.50 lbs (2.9 kg) |
| Weight Empty | 5.60 lbs (2.5 kg) |
| Buoyancy | 59.00 lbs (26.8 kg) |
| Master Pack Weight | 8.09 lbs (3.7 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

| | |
|--------------------|-----|
| Master Pack | 1 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES

1431
5 pc. Replacement Foam Set



1432
Strap Kit



1433
Replacement O-ring



1435
Padded Divider Set



1436
Office Divider Kit



1439
Lid Organizer



1430PF
Special Application Panel
Frame



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

