

# 1490CC2

#### Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Double safety locking latches with keys
- Fits notebook computers up to 17.3" L x 11.0" W x 3.3" D (43.94 x 27.94 x 8.38 cm)
- $\bullet$  Lid organizer and shoulder strap included (14.0" L x 10.8" W x 1.7" D notebooks will fit within the lid organizer)
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



#### DIMENSIONS

Interior (L×W×D) 17.75 x 11.37" x 4.12 (45.1 x 28.9 x 10.5 cm) Exterior (L×W×D) 19.87 x 13.93" x 4.68 (50.5 x 35.4 x 11.9 cm)

 Lid Depth
 1.50" (3.8 cm)

 Bottom Depth
 2.62" (6.7 cm)

 Total Depth
 4.12" (10.5 cm)

 Int Volume
 0.48 ft³ (0.014 m³)

#### **MATERIALS**

BodyABSLatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

# **COLOURS**



#### WEIGHT

 Weight With Foam
 6.50 lbs (2.9 kg)

 Weight Empty
 5.47 lbs (2.5 kg)

 Buoyancy
 41.00 lbs (18.6 kg)

 Master Pack Weight
 27.30 lbs (12.4 kg)

## **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

## **CERTIFICATIONS**

Def Stan 81-41

#### **OTHER**

Master Pack4NameplateyesMilitaryyes

## **ACCESSORIES**







**1498** Computer Lid Organizer



1472 Shoulder Strap



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 11-01-25