

SUPER-V-SERIES-3U

Super V

ЗU

- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- · Anti-reflective black hardware
- Coupling catches for secure stacking
- Choice of SAE 10-32 or Metric M6 clip nuts for even more flexibility in mounting equipment
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- High-strength steel rack frame supports equipment from 10 50 kg
- Designed to meet the requirements of Def Stan 81-41 Level J, Mil Standard 810, STANAG 4340 and other European standards.
- Designed to meet ANSI/EIA-310-C for universal rack mounting hole pattern
- 10 different models, frame heights 4-12U in two depths, 480 and 610mm
- · Lid hangers for lid storage while in use
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- REACH and RoHs compliant



DIMENSIONS

Exterior (L×W×D) 38.50 x 28.30" x 11.40 (97.8 x 71.9 x 29 cm)

 Rack Height
 5.25" (13.3 cm)

 Rack Depth
 24.00" (61 cm)

 Interior Lid Depth
 2.20" (5.6 cm)

 Interior Back Lid Depth
 5.20" (13.2 cm)

MATERIALS

Body RotoMolded Polyethylene

O-Ring Silicone Sponge
Purge Body Aluminum

Hardware Stainless Steel (Black Oxide) / RoHs Nickel Black

Frame Steel (Clear Coated)

COLOURS

Black

WEIGHT

Weight 50.00 lbs (22.7 kg)

Document created on 10-20-25