

1610 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1610 Standard



1614 With Padded Dividers



1610NF No Foam



1610TP With TrekPak Divider System



1610WF With Foam

DIMENSIONS

Interior (L×W×D) 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm) Exterior (L×W×D) 24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm) Lid Depth 2.05" (5.2 cm) Bottom Depth 8.57" (21.8 cm) Total Depth 10.62" (27 cm) Int Volume 2.23 ft ³ (0.063 m ³) Padlock Hole Diameter 0.31" (0.8 cm)		
Lid Depth 2.05" (5.2 cm) Bottom Depth 8.57" (21.8 cm) Total Depth 10.62" (27 cm) Int Volume 2.23 ft ³ (0.063 m ³)	Interior (L×W×D)	21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)
Bottom Depth 8.57" (21.8 cm) Total Depth 10.62" (27 cm) Int Volume 2.23 ft ³ (0.063 m ³)	Exterior (L×W×D)	24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm)
Total Depth 10.62" (27 cm) Int Volume 2.23 ft ³ (0.063 m ³)	Lid Depth	2.05" (5.2 cm)
Int Volume 2.23 ft ³ (0.063 m ³)	Bottom Depth	8.57" (21.8 cm)
	Total Depth	10.62" (27 cm)
Padlock Hole Diameter 0.31" (0.8 cm)	Int Volume	2.23 ft ³ (0.063 m ³)
	Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black

Desert Tan

OD Green

WEIGHT

Weight With Foam	22.30 lbs (10.1 kg)
Weight Empty	19.50 lbs (8.8 kg)
Buoyancy	119.93 lbs (54.4 kg)
Master Pack Weight	25.55 lbs (11.6 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67	
Def Stan 81-41	

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES



1609 Lid Organizer



1611 5 pc. Replacement Foam Set



1612 Pick N Pluck™ Sections Only (set of 3)

1507

Quick Mounts - set of 4





ner Defe Defe

1506TSA TSA Lock



1623 Replacement O-ring



1500D Desiccant Silica Gel



1610TPKIT TrekPak Case Divider Kit



1610TPDIV Extra TrekPak Dividers







1610MP EZ-Click™ MOLLE Panel

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 08-20-25