

1670

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 4 strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Two oversized fold down handles for extra grip



CONFIGURATIONS



1670 Standard



1670NF No Foam



1670WF With Foam



1674With Padded Dividers

DIMENSIONS

Interior (L×W×D) 28.10 x 16.49" x 9.19 (71.4 x 41.9 x 23.3 cm) Exterior (L×W×D) 31.04 x 19.39" x 11.17 (78.8 x 49.3 x 28.4 cm)

 Lid Depth
 1.80" (4.6 cm)

 Bottom Depth
 7.39" (18.8 cm)

 Total Depth
 9.19" (23.3 cm)

 Int Volume
 2.46 ft³ (0.07 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

BodyPolypropyleneLatchABSO-RingPolymerPinsStainless Steel

Foam 1.3 lb Polyurethane

Purge Body AB

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 26.00 lbs (11.8 kg)

 Weight Empty
 23.00 lbs (10.4 kg)

 Buoyancy
 182.00 lbs (82.6 kg)

 Master Pack Weight
 49.00 lbs (22.2 kg)


TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

OTHER

Wheels 4 Master Pack 1

ACCESSORIES



1671 4 pc. Replacement Foam Set



1675 Padded Divider Set



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 08-26-25