

1750

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click™ MOLLE Panels
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles



CONFIGURATIONS



DIMENSIONS

Interior (L×W×D) 50.38 x 13.33" x 5.33 (128 x 33.9 x 13.5 cm) Exterior (L×W×D) 53.60 x 16.05" x 6.13 (136.1 x 40.8 x 15.6 cm)

 Int Volume
 2.07 ft³ (0.059 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 26.70 lbs (12.1 kg)

 Weight Empty
 21.00 lbs (9.5 kg)

TEMPERATURE

 $\begin{array}{ll} \mbox{Minimum Temperature} & -40\mbox{°F} \ (-40\mbox{°C}) \\ \mbox{Maximum Temperature} & 210\mbox{°F} \ (98.9\mbox{°C}) \\ \end{array}$

OTHER

Nameplate yes

ACCESSORIES



1500MP EZ-Click™ MOLLE Panel



1506TSA TSA Lock



1500D Desiccant Silica Gel



1753 Replacement O-ring

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 04-25-24