



1400 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware
- Stainless steel padlock protectors



CONFIGURATIONS



1400
Standard



1400NF
No Foam



1400WF
With Foam

DIMENSIONS

Interior (L×W×D)	11.81 x 8.87" x 5.18 (30 x 22.5 x 13.2 cm)
Exterior (L×W×D)	13.37 x 11.62" x 6.00 (34 x 29.5 x 15.2 cm)
Lid Depth	1.18" (3 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	5.18" (13.2 cm)
Int Volume	0.31 ft ³ (0.009 m ³)
Padlock Hole Diameter	5/16" (8 mm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

Purge Vent

3 Micron Hydrophobic Non-Woven

COLOURS

■ Black
■ Silver

■ Desert Tan
■ Yellow

■ Orange

■ OD Green

WEIGHT

Weight With Foam	4.41 lbs (2 kg)
Weight Empty	3.97 lbs (1.8 kg)
Buoyancy	20.06 lbs (9.1 kg)
Master Pack Weight	22.60 lbs (10.3 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
STANAG 4280
ATA 300

FOAM PROPERTIES

Layer 1 (Lid)	1.38" Convolute
Layer 2 (Base)	0.50" Pad
Layer 3 (Base)	3.38" Pick N Pluck

OTHER

Master Pack	4
Nameplate	yes
Military	yes

ACCESSORIES



1401
3 pc. Replacement Foam Set



1403
Replacement O-ring



1400PF
Special Application Panel
Frame



PL2
Padlock (2 pack)



1400TPKIT
TrekPak Case Divider Kit



1400TPDIV
Extra TrekPak Dividers



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-23-20