



1470

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Double safety locking latches with keys**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1470
Standard



1470NF
No Foam



1470WF
With Foam

DIMENSIONS

Interior (LxWxD)	15.70 x 10.70" x 3.87 (39.9 x 27.2 x 9.8 cm)
Exterior (LxWxD)	16.88 x 13.23" x 4.47 (42.9 x 33.6 x 11.4 cm)
Lid Depth	1.47" (3.7 cm)
Bottom Depth	2.40" (6.1 cm)
Total Depth	3.87" (9.8 cm)
Int Volume	0.38 ft ³ (0.011 m ³)

MATERIALS

Body	ABS
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	5.51 lbs (2.5 kg)
Weight Empty	4.28 lbs (1.9 kg)
Buoyancy	24.91 lbs (11.3 kg)
Master Pack Weight	22.20 lbs (10.1 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

MIL C-4150J

OTHER

Master Pack	4
Nameplate	yes
Military	yes

ACCESSORIES



1471
3 pc. Replacement Foam Set



1472
Shoulder Strap



1473
Replacement O-ring



1470PF
Special Application Panel Frame



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 06-28-22