

9415i

9410L + Safety = 9415i Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 392 lumens, the 9415i LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 392 meters. And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety certified for the most volatile work areas, the 9415i LED Lantern is safe and one of the most compact, high output lanterns on the market.

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Carrying Strap included



DIMENSIONS

Length

8.75" (22.2 cm)

MATERIALS

Body	Anti-static Impact Modified PC/PBT	
O-Ring	EPDM	
Lens	Anti-static coated Polycarbonate (PC)	
Shroud	Anti-static Impact Modified PC/PBT	

COLOURS

High Visibility Yellow

LIGHT SPECS

POWER

С
NiMH
4
yes
yes
15 hrs
RGB LED
4.8v

WEIGHT

Weight With Batteries58.2 oz (1650 gr)Weight Without
Batteries0.0 oz (0 gr)

SWITCH

Switch Type Light Modes Push Button High / Low / Flashing

1 B

CERTIFICATIONS

IECEx ia ATEX Zone 0 InMetro

OTHER

Minimum Pack Package Code

FL1 STANDARD	HIGH	LOW
	392 LUMENS	144 LUMENS
	4h 30mins	11h 0mins
	392m	234m
	32767cd	13747cd
	IPX4	

ACCESSORIES



94166061F8056FDeck/Dash Charger Base UnitDirect Wiring Rig for Fast Charger12v Plug-in for Fast Charger

9418Z0 Replacement Battery

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 10-23-24