



3315R

Ultra compact, special designed lithium rechargeable and safety certified make the Pelican™ 3315R one of the most versatile work lights available today. Its compact design fits comfortably in your hand and requires little space for storage or transport. The 3315R produces up to 132 lumens and provides up to 34 hours of continuous run time. 3 modes are provided, High / Low / Flashing. There is a full time battery level indicator built into the power switch so you'll always know when it's time to recharge. Additionally, there is a right angle adapter accessory (sold separately) that provides hands free lighting. The right angle adapter also allows the light head to articulate, directing the light exactly where you need it.

- IPX7 Waterproof
- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Safety Certified Class I, Division 1 / IECEx ia
- Lanyard (included)
- Articulating right angle adapter with clip (sold separately)
- Special Lithium rechargeable battery provides 2,000 cycles (a 300% increase)
- Up to 132 Lumens
- Up to 34 hours, 15 minutes run time




DIMENSIONS

Length	6.11" (15.5 cm)
---------------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	EPDM
Lens	Anti-static coated Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT

COLOURS

-  High Visibility Yellow

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER

Battery Size	18650
Battery Type	Lithium Iron Phosphate
Battery Quantity	1
Batteries Included	yes
Rechargeable	yes
Charge Time	10 hrs
Battery Level Indicator	RGB LED
Volts	3.2v

WEIGHT

Weight With Batteries	4.6 oz (130 gr)
Weight Without Batteries	3.0 oz (85 gr)

SWITCH






Switch Type	Push Button
Light Modes	High / Low / Flashing

CERTIFICATIONS

Class I, Division 1
IECEX ia
InMetro

OTHER

Minimum Pack	1
Package Code	C

FL1 STANDARD	HIGH	LOW
	132 LUMENS	15 LUMENS
	5h 0mins	34h 0mins
	108m	35m
	2931cd	308cd
	IP67	

ACCESSORIES



3317
Right Angle Adapter



8056F
12v Plug-in for Fast Charger



3318
Deck/Dash Charger Base Unit



2467F
110V Transformer (USA)



6061F
Direct Wiring Rig for Fast Charger



2468A
220V Transformer (Australia)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-20-24