



2785

Headlamp

At long last, a high performance / long run time safety certified headlamp! The Class I, Division 1 / IECEx certified 2785 provides a Main, Downcast, Flashing, and combination LED modes. The focused Main LED provides a great distance beam while the Downcast LED projects a dispersed beam set at a 45° downward angle. This "Downcast" beam offers a number of benefits including safer illuminated pathways, reading capability, as well as convenient face to face applications. Options are plentiful as each mode is provided in an easy to select high, medium or low setting. The rear mounted battery pack is equipped with a full time battery level indicator in addition to a rear facing red LED for added safety. With over 200 lumens of high intensity light output available, coupled with the ability to last up to 100 hours in the low setting, the 2785 will support virtually all your hands free lighting needs. All this in a product that carries intrinsically safe certifications.

- 4 AA Batteries Included
- Pivoting Head For Directional Beam (60°)
- Rear Mounted Red LED
- Dual Beams including Downcast LED Technology
- 3 Light Levels
- Full Time Battery Level Indication
- Cloth and Rubber Straps Included



DIMENSIONS

| | |
|---------------|----------------|
| Length | 3.00" (7.6 cm) |
|---------------|----------------|

MATERIALS

| | |
|---------------|--------------------|
| Body | Polycarbonate (PC) |
| O-Ring | Gasket |
| Lens | Polycarbonate (PC) |
| Shroud | Polycarbonate (PC) |

COLOURS

| | |
|---|--|
|  Black |  High Visibility Yellow |
|---|--|

LIGHT SPECS

| | |
|----------------------------|-----|
| Lamp Type | LED |
| Lamp Secondary Type | LED |

POWER

| | |
|--------------------------------|-------------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 4 |
| Batteries Included | yes |
| Battery Level Indicator | 3 Blue LEDs |
| Volts | 6.0v |

WEIGHT

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
Weight With Batteries 8.8 oz (249 gr) sales@pelican.com • www.pelican.com
Weight Without Batteries 6.6 oz (187 gr)






Document created on 09-21-24

SWITCH

Switch Type Rotary / Push Button
Light Modes High / Medium / Low / Downcast / Spot / Flashing

CERTIFICATIONS

Class I, Division 1
IECEX ia

| FL1 STANDARD | MAIN HIGH | MAIN MED | MAIN LOW |
|---|---------------|---------------|--------------|
|  | 215 LUMENS | 106 LUMENS | 22 LUMENS |
|  | 5h 0mins | 13h 0mins | 98h 0mins |
|  | 108m | 76m | 34m |
|  | 2911cd | 1445cd | 290cd |
|  | IP54 | | |

ACCESSORIES