



## 472-FLD-DESK-TA

### Mobile Office™

#### Field Desk

The Pelican roto molded single field desk provides one (1) flat desk working surface that attaches to the left side of the base case. It includes black plated steel catch and strike hardware, two (2) large injection molded handles, one (1) green fabric chair and 6 drawers (2 small lockable top drawers and 2 medium and 2 large drawers both deep enough for Pendaflex folder hangers). The desk easily folds into one shipping container. Power strip provided by customer.

- One (1) Flat desk surface (30" x 28.5") for installation on the left side of the base drawer case
- Two (2) large injection molded handles
- Black Plated Steel Catch and Strike Hardware
- Six drawers in the base case
- Two (2) small drawers with a shared locking hasp, padlock not included. Left Side: L14" x W 8.8" x D 3.5" Right Side: L14" x W 12.5" x D 3.5"
- Two (2) medium drawers for Pendaflex folders (Left Side: L14" x W 8.8" x D 9.75")
- Two (2) large drawers for Pendaflex folders (Right Side: L14" x W 12.5" x D 9.75")
- Power strip provided by customer
- One (1) Fabric Field Chair (max. 300 lb./136kg). Folded chair stores in the lid





#### DIMENSIONS

<b>Exterior (LxWxD)</b>	30.70 x 21.00" x 28.50 (78 x 53.3 x 72.4 cm)
-------------------------	--

#### MATERIALS

<b>Body</b>	RotoMolded Polyethylene
<b>Latch</b>	Steel (Nickel-black Plated)
<b>O-Ring</b>	Silicone Sponge
<b>Pins</b>	Stainless Steel
<b>Purge Body</b>	Aluminum
<b>Hardware</b>	Black Cobalt

#### COLOURS

 Black	 Desert Tan	 Gray	 OD Green
---	--	--	---

#### WEIGHT

<b>Weight</b>	81.30 lbs (36.9 kg)
---------------	---------------------

#### TEMPERATURE

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 04-24-24*