

70QT Elite

Pelican Products, Inc. has protected defense, emergency and scientific expedition equipment through some ofthe harshest conditions on Earth since 1976. This same DNA is now available to you in Pelican[™] Elite Coolers.

We hold ourselves to higher criteria than other cooler makers. When it comes to durability, performance and ergonomic design, just "good enough" doesn't cut it. As a result, Pelican™ Elite Coolers perform to higher standards — better than any cold locker, tougher than any icebox. Pelican™ Elite Coolers are true next-generation innovations, created to last a lifetime. From the latches to the freezer-grade seal to the toughest handles in the business, every part is engineered to our extreme durability and performance standards. Which is why we feel confident in providing you with a Lifetime Guarantee. Not three years. Not five years. A lifetime. Something the other makers don't (or can't) do.

Whether you're on the hunt of a lifetime, far out at sea with a cooler full of catch, crossing deserts on safari or simply tailgating during a big game – the Pelican[™] Elite Cooler is the one for you.



- Extreme ice retention
- Press & Pull Latches
- Non-Skid & Non-Marking Raised Feet
- Molded-In Lock Hasp, Stainless Steel Plate
- Guaranteed for life
- Integrated Cup Holders
- Built-in Bottle Opener

DIMENSIONS

Interior (L×W×D)	23.50 x 11.00" x 14.30 (59.7 x 27.9 x 36.3 cm)
Exterior (L×W×D)	36.00 x 20.30" x 21.00 (91.4 x 51.6 x 53.3 cm)
Volume	72.42QT (68.53 L)
Can Capacity	53 cans
Int Volume	2.14 ft³ (0.061 m³)
Insulation Thickness	2.00" (5.1 cm)

MATERIALS

Body	Polypropylene	
Latch	ABS	
Handle	Polypropylene	
Spigot	Polypropylene	
Hardware	Stainless Steel	
Insulation	Polyurethane Foam	

COLOURS

White - Gray Hunter Green / Tan Dark Gray - Green

Sage / Gray

Cement / White

WEIGHT

Weight

ACCESSORIES



 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 09-14-25